

# **DEPENDABLE PEST MANAGEMENT**

### Steri- Fab

**COMMON NAME:** phenothrin; isopropyl alcohol (Steri-Fab)

**STATEMENT OF PRACTICAL TREATMENT:** If swallowed, call a poison control center or doctor immediately. If inhaled, move person to fresh air and call a poison control center or doctor for treatment advice. If on skin or clothing, take off clothing and rinse skin immediately for 15-20 minutes. Call a poison control center or doctor for treatment advice. If in eyes, hold eye open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice

**PRECAUTIONARY STATEMENT**: Harmful if inhaled. Causes eye and skin irritations. Do not breathe vapors or spray mist. Do not get in eyes. Avoid contact with skin.

113 Flatland Rd, Chestertown, MD 21620 | Kent-410.778.5658 | Queen Anne's-410.758.1057 | Cecil-443.282.0017 | Fax-410.810.8822

#### Material Safety Data Sheet U.S Department of Labor

May be used to comply with Occupational Safety & Health Administration OSHA's Hazard Communication Standard. (Non-Mandatory Form) 29 CFR 1910.1200. Standard must be consulted Form Approved for specific requirements. OMB No. 1218-0072

IDENTITY (As Used on Label and List) STERI FAB ®

### SECTION I: EPA REG NO. 397-13

Manufacturer's Name: NOBLE PINE PRODUCTS CO. Address: P.O. BOX 41 - CENTUCK STATION

YONKERS, NY 10710

Emergency Telephone Number: 800-424-9300 (Chemtrec) Telephone Number for Information: 914-664-5877

Date Prepared: January 1, 2007

### SECTION II: - HAZARDOUS INGREDIENTS/IDENTIFY INFORMATION

Hazardous Components (Specific Chemical Identity; Common Name(s)): ISOPROPANOL

OSHA PEL: STEL ACGIH TLV: 500 PPM

OTHER LIMITS RECOMMENDED: STEL 500 PPM

96 (OPTIONAL) 60.39

HMIS RATING AS FOLLOWS:

HEALTH: 1 FLAMMABILITY: 3 REACTIVITY: 0

SPECIAL PRECAUTIONS: NONE

### SECTION III:- PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: APPROX. 177F

VAPOR PRESSURE (mm Hg): GREATER THAN 59mm

VAPOR DENSITY (AIR=1): APPROX. 0.60 SPECIFIC GRAVITY (H2O=1): LESS THAN 1

MELTING POINT: N/A

EVAPORATION RATE (Butyl Acetate=1): LESS THAN 1

SOLUBILITY IN WATER: DISPERSIBLE

APPEARANCE AND ODOR: Crystal Clear. Slightly Cloudy on Agitation - Mild Alcohol Odor.

## SECTION IV:- FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used): ( 83 ° F ) Pensky Martens Closed

FLAMMABLE LIMITS: For Isopropanol Approx.

LEL: 2.5% UEL: By Volume

EXTINGUISHING MEDIA: Water or Dry Chemical SPECIAL FIRE FIGHTING PROCEDURES: NONE

UNUSUAL FIRE & EXPLOSION HAZARDS: Flammable Upon Application Of An Ignition Source.

### SECTION V:- REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (Materials to Avoid): Acid Materials Or Strong Oxidizing Agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: N/A HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

### SECTION VI: - HEALTH HAZARDS DATA (SF)

ROUTE(S) OF ENTRY: INHALATION: YES

SKIN: YES

INGESTION: UNLIKELY IN APPLICATION

#### HEALTH HAZARDS (Acute and Chronic):

- HARMFUL IF SWALLOWED.
- AVOID INHALATION OF VAPORS.
- AVOID CONTACT WITH SKIN AND EYES.
- WASH CONTAMINATED SKIN PROMPTLY WITH SOAP & WARM WATER.
- CONSULT PHYSICIAN IF IRRITATION PERSISTS.

CARCINOGENICITY: NO NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

SIGNS AND SYMPTOMS OF EXPOSURE: N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/A

EMERGENCY & FIRST AID PROCEDURES: Flush Eyes or Skin With Plenty Of Water For At least 15 minutes. For Eyes Get Medical Attention. For Inhalation: Remove from Exposure.

### SECTION VII:- PROCEDURES FOR SAFE HANDLING & USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Flush Area With Plenty Of Water.

#### WASTE DISPOSAL METHOD:

Dilute And Discharge In Accordance With Local, State, And Federal Regulations.

#### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

- Store in Cool Dry Place.
- Keep Containers Closed And Away From Heat or Flame.

#### OTHER PRECAUTIONS:

Do Not Use Or Store Near Open Flame.

### SECTION VIII:

CONTROL MEASURES:

None Required If Good Ventilation Is Maintained.

#### RESPIRATORY PROTECTION (specific Type)

If Required, OSHA/NIOSH Approved Breathing Apparatus.

VENTILATION

LOCAL EXHAUST: Apply In Well Ventilated Area.

SPECIAL: N/A

MECHANICAL(General) N/A

OTHER N/A

PROTECTIVE GLOVES: NONE REQUIRED EYE PROTECTION: NONE REQUIRED

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: NONE REQUIRED

WORLD/HYGIENIC PRACTICES: N/A